



Dog Feeder Assembly Instructions

Your new dog feeder has been packaged flat for ease of shipping. It can be assembled in 1-3 easy steps using Knapp Mod-eez connectors. The Mod-eez connectors consist of two pieces. An open ended bracket and a double-headed screw which slides into the bracket. These may take some effort to seat fully and will be easier with a rubber mallet or a hammer. If using a hammer place a folded towel over the wood and use light taps to prevent damage.

Before assembly please identify parts that will be connected. All feeders consist of two legs and a top. The Medium and Large feeders have a stretcher than spans between the two legs for stability due to their height.

Bracket



Screw



Step 1 (Medium and Large only) – Hold one leg upright and place stretcher bracket over screw about a third of the way from the bottom of stretcher. Once stretcher is flush with leg, press down until the piece is fully seated.



Step 2 (Medium and Large only) – Repeat the previous step on the other leg. You should now have the base assembled which should look like the picture below.



Step 3 - Place top upside down with logo at the bottom right corner. Align each leg over the screw with bracket openings facing you. Pull towards you to seat each leg fully.



Flip feeder over, place bowl in opening, and hang name tag.
Congratulations!! Your new dog feeder is ready to use.



Thank You,

Heather and Billy
B Squared Woodworking, LLC
(844) 277-9663
<https://bsquaredwoodworking.com>